

MBC : Madreviti in bronzo cilindriche

Tolleranza filettatura :
7H (ISO 2903)

Legenda:


D = diametro boccola

L = lunghezza boccola

Tolleranze sulla boccola :

D = h 7

L = +/- 0,1 mm



Codice articolo	Filetto	verso	D mm	L mm	massa gr	Superficie di supporto in mm ²	Rendimento dinamico
MBC10031D	Tr10x03	dx	20	20	50	480,66	0,35
MBC12031D	Tr12x03	dx	36	36	250	593,76	0,35
MBC12031S	Tr12x03 LH	sx	36	36	250	593,76	0,35
MBC14041D	Tr14x04	dx	36	36	245	678,58	0,37
MBC14041S	Tr14x04 LH	sx	36	36	245	678,58	0,37
MBC16041D	Tr16x04	dx	36	36	230	791,68	0,37
MBC16041S	Tr16x04 LH	sx	36	36	230	791,68	0,37
MBC18041D	Tr18x04	dx	36	36	220	904,77	0,34
MBC18041S	Tr18x04 LH	sx	36	36	220	904,77	0,34
MBC20041D	Tr20x04	dx	40	40	367	1130,97	0,33
MBC20041S	Tr20x04 LH	sx	40	40	367	1130,97	0,33
MBC22051D	Tr22x05	dx	40	40	285	1225,22	0,29
MBC22051S	Tr22x05 LH	sx	40	40	280	1225,22	0,29
MBC25051D	Tr25x05	dx	45	45	492	1590,43	0,29
MBC25051S	Tr25x05 LH	sx	45	45	492	1590,43	0,29
MBC28051D	Tr28x05	dx	45	45	360	1802,48	0,28
MBC28051S	Tr28x05 LH	sx	45	45	360	1802,48	0,28
MBC30061D	Tr30x06	dx	50	50	520	2120,57	0,30
MBC30061S	Tr30x06 LH	sx	50	50	515	2120,57	0,30
MBC35061D	Tr35x06	dx	55	55	650	2764,60	0,27
MBC35061S	Tr35x06 LH	sx	55	55	650	2764,60	0,27
MBC36061D	Tr36x06	dx	55	55	638	2 851,00	0,27
MBC36061S	Tr36x06 LH	sx	55	55	638	2 851,00	0,27
MBC40071D	Tr40x07	dx	60	60	800	3440,04	0,28
MBC40071S	Tr40x07 LH	sx	60	60	795	3440,04	0,28
MBC45081D	Tr45x08	dx	65	65	960	4186,17	0,28
MBC45081S	Tr45x08 LH	sx	65	65	960	4186,17	0,28
MBC50081D	Tr50x08	dx	70	70	1110	5057,96	0,25
MBC50081S	Tr50x08 LH	sx	70	70	1110	5057,96	0,25
MBC55091D	Tr55x09	dx	80	80	1760	6346,01	0,26
MBC60091D	Tr60x09	dx	80	80	1500	6974,33	0,25
MBC60091S	Tr60x09 LH	sx	80	80	1500	6974,33	0,25
MBC70101D	Tr70x10	dx	100	100	3875	10210,17	0,24